



RF Solution offer a wide selection of Coaxial Low PIM Termination for global customers. CT-200W-FX1720-IP65-DINK-0.35-4G is a Coaxial Low PIM Termination in Frequency Range of DC 0.35~4.0 GHz. It is made of high quality materials under a high standard, the Connector Type of this product is DIN-F (K), VSWR Max is 1.25 and Impedance is 50 Ω. The component has a good working performance and stability, it is ideal for handling a Power of 200 W.

Product Details

| | |
|-------------|---|
| Part Number | CT-200W-FX1720-IP65-DINK-0.35-4G |
| Description | DC 0.35~4.0 GHz Coaxial Low PIM Termination |

General Parameters

| | |
|-----------------------|----------------------------------|
| Frequency Range | DC 0.35~4.0 GHz |
| Connector Type | DIN-F (K) |
| VSWR Max | 1.25 |
| Impedance | 50 Ω |
| Power | 200 W |
| PIM3 Max | -150dBc/-155dBc/-160dBc @2*43dBm |
| Waterproof Grade | IP65/IP67 |
| Size | 200*170*64 mm |
| Weight | / |
| Color | Black |
| Operating Temperature | -35~+75 °C |
| Storage Temperature | / |
| ROHS Compliant | Yes |

Outline Drawing (mm)

