



RF Solution offer a wide selection of Low Pass Filter for global customers. LPF-DCM4500A-S is a Low Pass Filter in Frequency Range of DC~4500 MHz. It is made of high quality materials under a high standard, the Insertion Loss Max of this product is 2.0 dB, Rejection Min is 40dB@4452-21000MHz and VSWR Max is 2.00. The component has a good working performance and stability, it is ideal for handling a Rated Power of 20 W.

### Product Details

|             |                             |
|-------------|-----------------------------|
| Part Number | LPF-DCM4500A-S              |
| Description | DC~4500 MHz Low Pass Filter |

### General Parameters

|                       |                      |
|-----------------------|----------------------|
| Frequency Range       | DC~4500 MHz          |
| Insertion Loss Max    | 2.0 dB               |
| Rejection Min         | 40dB@4452-21000MHz   |
| VSWR Max              | 2.00                 |
| Rated Power           | 20 W                 |
| Impedance             | 50 Ω                 |
| Connector Type        | SMA-F                |
| Size                  | 56*22*12 mm          |
| Weight                | /                    |
| Surface Finishing     | Black Painting       |
| Operating Temperature | Ordinary Temperature |
| Storage Temperature   | -55~+85 °C           |
| ROHS Compliant        | Yes                  |

### Outline Drawing (mm)

