

RF Solution offer a wide selection of 2 Ways Power Divider for global customers. PD02-F3034-S-2-8GHz is a 2 Ways Power Divider in Frequency Range of 2.0~8.0 GHz. It is made of high quality materials under a high standard, the Insertion Loss Max of this product is 0.6 dB, Isolation Min is 20 dB and Amplitude Unbalance is ± 0.3 dB. The component has a good working performance and stability, it is ideal for handling a Forward Power of 20 W.

Product Details

Part Number	PD02-F3034-S-2-8GHz
Description	2.0~8.0 GHz 2 Ways Power Divider

General Parameters

Frequency Range	2.0~8.0 GHz
Insertion Loss Max	0.6 dB
Isolation Min	20 dB
Amplitude Unbalance	±0.3 dB
Forward Power	20 W
Reverse Power	2 W
VSWR Input Max	1.30
VSWR Output Max	1.20
Phase Unbalance	± 3°
Impedance	50 Ω
Connector Type	SMA-F
Size	30*34*10 mm
Weight	1
Surface Finishing	Grey Painting



PD02-F3034-S-2-8GHz

2.0~8.0 GHz 2 Ways Power Divider

Operating Temperature	-45~+85 °C
ROHS Compliant	Yes

Outline Drawing (mm)

