



RF Solution offer a wide selection of 2 Ways Power Divider for global customers. PD02-F4460-S-698-6000MHz is a 2 Ways Power Divider in Frequency Range of 698~6000 MHz. It is made of high quality materials under a high standard, the Insertion Loss Max of this product is 1.5 dB, Split Loss is 3.0 dB and Isolation Min is 18 dB. The component has a good working performance and stability, it is ideal for handling a Rated Power of 50 W.

Product Details

| | |
|-------------|-----------------------------------|
| Part Number | PD02-F4460-S-698-6000MHz |
| Description | 698~6000 MHz 2 Ways Power Divider |

General Parameters

| | |
|-----------------------|----------------|
| Frequency Range | 698~6000 MHz |
| Insertion Loss Max | 1.5 dB |
| Split Loss | 3.0 dB |
| Isolation Min | 18 dB |
| Rated Power | 50 W |
| VSWR Max | 1.40 |
| Waterproof Grade | IP65 |
| Relative Humidity Max | 95% |
| Impedance | 50 Ω |
| Connector Type | SMA-F |
| Size | 60*44*15 mm |
| Weight | / |
| Surface Finishing | Black Painting |
| Operating Temperature | -20~+60 °C |



ROHS Compliant

Yes

Outline Drawing (mm)

