



RF Solution offer a wide selection of 8 Ways Power Divider for global customers. PD08-F1190-S-700-3000MHz is a 8 Ways Power Divider in Frequency Range of 700~3000 MHz. It is made of high quality materials under a high standard, the Insertion Loss Max of this product is 2.0 dB, Isolation Min is 18 dB and Amplitude Unbalance is ± 0.5 dB. The component has a good working performance and stability, it is ideal for handling a Forward Power of 20 W.

Product Details

| | |
|-------------|-----------------------------------|
| Part Number | PD08-F1190-S-700-3000MHz |
| Description | 700~3000 MHz 8 Ways Power Divider |

General Parameters

| | |
|---------------------|---------------|
| Frequency Range | 700~3000 MHz |
| Insertion Loss Max | 2.0 dB |
| Isolation Min | 18 dB |
| Amplitude Unbalance | ± 0.5 dB |
| Forward Power | 20 W |
| Reverse Power | 1 W |
| VSWR Input Max | 1.50 |
| VSWR Output Max | 1.40 |
| Phase Unbalance | $\pm 5^\circ$ |
| Impedance | 50 Ω |
| Connector Type | SMA-F |
| Size | 108*90*10 mm |
| Weight | / |
| Surface Finishing | Grey Painting |



| | |
|-----------------------|------------|
| Operating Temperature | -45~+85 °C |
| ROHS Compliant | Yes |

Outline Drawing (mm)

