



RF Solution offer a wide selection of Leaded Attenuator for global customers. RFT20N-60AM6363-6 is a Leaded Attenuator in Frequency Range of DC~6.0 GHz. It is made of high quality materials under a high standard, the Attenuation Value of this product is 20 dB, Attenuation Tolerance is ± 0.8 dB and VSWR Max is 1.25. The component has a good working performance and stability, it is ideal for handling a Rated Power of 60 W.

Product Details

| | |
|-------------|------------------------------|
| Part Number | RFT20N-60AM6363-6 |
| Description | DC~6.0 GHz Leaded Attenuator |

General Parameters

| | |
|-----------------------------|--------------------------------|
| Frequency Range | DC~6.0 GHz |
| Attenuation Value | 20 dB |
| Attenuation Tolerance | ± 0.8 dB |
| VSWR Max | 1.25 |
| Rated Power | 60 W |
| Impedance | 50 Ω |
| Temperature Coefficient Max | 150 ppm/ $^{\circ}$ C |
| Size | Refer to the design drawing |
| Substrate Material | AlN |
| Porcelain Hat Material | Al ₂ O ₃ |
| Lead | 99.99% Sterling Silver |
| Resistance Technology | Thick Film |
| Operating Temperature | -55 to +150 $^{\circ}$ C |
| ROHS Compliant | Yes |



Outline Drawing (mm)

