



RF Solution offer a wide selection of Microstrip Attenuator for global customers. RFTXX-05MA4563-18 is a Microstrip Attenuator in Frequency Range of DC~18.0 GHz. It is made of high quality materials under a high standard, the Attenuation Value of this product is ①1-10 dB ②11-20 dB ③21-30 dB, Attenuation Tolerance is ①±0.7 dB ②±0.8 dB ③± 1.0 dB and VSWR Max is 1.25 type 1.3. The component has a good working performance and stability, it is ideal for handling a Rated Power of 5 W.

Product Details

Part Number	RFTXX-05MA4563-18
Description	DC~18.0 GHz Microstrip Attenuator

General Parameters

Frequency Range	DC~18.0 GHz
Attenuation Value	①1-10 dB ②11-20 dB ③21-30 dB
Attenuation Tolerance	①±0.7 dB ②±0.8 dB ③± 1.0 dB
VSWR Max	1.25 type 1.3
Rated Power	5 W
Impedance	50 Ω
Size	6.35*4.5*0.5 mm
Temperature Coefficient Max	150 ppm/°C
Substrate Material	BeO
Resistance Process	Thick Film
Operating Temperature	-55~+150 °C
Storage Temperature	/
ROHS Compliant	Yes

Outline Drawing (mm)

