



RF Solution offer a wide selection of Microstrip Attenuator with Sleeve for global customers. RFTXX-10TA7310-18 is a Microstrip Attenuator with Sleeve in Frequency Range of DC~18.0 GHz. It is made of high quality materials under a high standard, the Attenuation Value of this product is ①01-10 dB ②11-20 dB ③21-30 dB, Attenuation Tolerance is ①±0.5 dB ②±0.6 dB ③± 1.0 dB and VSWR Max is 1.25 type 1.3. The component has a good working performance and stability, it is ideal for handling a Power of 10 W.

### Product Details

Part Number	RFTXX-10TA7310-18
Description	DC~18.0 GHz Microstrip Attenuator With Sleeve

### General Parameters

Frequency Range	DC~18.0 GHz
Attenuation Value	①01-10 dB ②11-20 dB ③21-30 dB
Attenuation Tolerance	①±0.5 dB ②±0.6 dB ③± 1.0 dB
VSWR Max	1.25 type 1.3
Power	10 W
Impedance	50 Ω
Size	Φ7.35*10.2 mm
Temperature Coefficient Max	150 ppm/°C
Substrate Material	BeO
Sleeve Material	Al (Conductive oxidation)
Resistance Process	Thick Film
Operating Temperature	-55 ~+125°C
ROHS Compliant	Yes



### Outline Drawing (mm)

