



RF Solution offer a wide selection of Flanged Attenuator for global customers. RFTXX-150AM2310-6 is a Flanged Attenuator in Frequency Range of DC~6.0 GHz. It is made of high quality materials under a high standard, the Attenuation Value of this product is ①01-10 dB②15,17,20,21 dB③19 dB ④23,24 dB, Attenuation Tolerance is ①±0.8 dB②+0.5/-1.5 dB③+0.5/-2.0 dB ④±1.0 dB and VSWR Max is 1.25. The component has a good working performance and stability, it is ideal for handling a Rated Power of 150 W.

Product Details

Part Number	RFTXX-150AM2310-6
Description	DC~6.0 GHz Flanged Attenuator

General Parameters

Frequency Range	DC~6.0 GHz
Attenuation Value	①01-10 dB②15,17,20,21 dB③19 dB ④23,24 dB
Attenuation Tolerance	①±0.8 dB②+0.5/-1.5 dB③+0.5/-2.0 dB ④±1.0 dB
VSWR Max	1.25
Rated Power	150 W
Impedance	50 Ω
Temperature Coefficient Max	150 ppm/°C
Size	Refer to the design drawing
Substrate Material	BeO
Porcelain Hat Material	Al2O3
Flange	Nickel-plated Copper
Lead	99.99% Sterling Silver
Resistance Technology	Thick Film
Operating Temperature	-55 to +150 °C

ROHS Compliant

Yes

Outline Drawing (mm)

