



RF Solution offer a wide selection of Flanged Attenuator for global customers. RFTXX-150AM2510-3 is a Flanged Attenuator in Frequency Range of DC~3.0 GHz. It is made of high quality materials under a high standard, the Attenuation Value of this product is ①25,26,27 dB②30 dB, Attenuation Tolerance is ①+0.8/-1.5 dB②±1.0 dB and VSWR Max is 1.25. The component has a good working performance and stability, it is ideal for handling a Rated Power of 150 W.

Product Details

Part Number	RFTXX-150AM2510-3
Description	DC~3.0 GHz Flanged Attenuator

General Parameters

Frequency Range	DC~3.0 GHz
Attenuation Value	①25,26,27 dB②30 dB
Attenuation Tolerance	①+0.8/-1.5 dB②±1.0 dB
VSWR Max	1.25
Rated Power	150 W
Impedance	50 Ω
Temperature Coefficient Max	150 ppm/°C
Size	Refer to the design drawing
Substrate Material	BeO
Porcelain Hat Material	Al ₂ O ₃
Flange	Nickel-plated Copper
Lead	99.99% Sterling Silver
Resistance Technology	Thick Film
Operating Temperature	-55 to +150 °C

ROHS Compliant

Yes

Outline Drawing (mm)

