



RF Solution offer a wide selection of Microstrip Attenuator with Sleeve for global customers. RFTXX-20TA7322-18 is a Microstrip Attenuator with Sleeve in Frequency Range of DC~18.0 GHz. It is made of high quality materials under a high standard, the Attenuation Value of this product is ①01-10 dB ②11-20 dB ③21-30 dB ④35/40/50/60 dB, Attenuation Tolerance is ①±0.5 dB ②±0.6 dB ③± 1.0 dB ④± 1.5 dB and VSWR Max is 1.25 type 1.3. The component has a good working performance and stability, it is ideal for handling a Power of 20 W.

Product Details

Part Number	RFTXX-20TA7322-18
Description	DC~18.0 GHz Microstrip Attenuator With Sleeve

General Parameters

Frequency Range	DC~18.0 GHz
Attenuation Value	①01-10 dB ②11-20 dB ③21-30 dB ④35/40/50/60 dB
Attenuation Tolerance	①±0.5 dB ②±0.6 dB ③± 1.0 dB ④± 1.5 dB
VSWR Max	1.25 type 1.3
Power	20 W
Impedance	50 Ω
Size	Φ7.35*22.2 mm
Temperature Coefficient Max	150 ppm/°C
Substrate Material	BeO
Sleeve Material	Al (Conductive oxidation)
Resistance Process	Thick Film
Operating Temperature	-55 ~+125°C
ROHS Compliant	Yes



Outline Drawing (mm)

