



RF Solution offer a wide selection of Leaded Attenuator for global customers. RFTXX-250AM1010-1.5 is a Leaded Attenuator in Frequency Range of DC~1.5 GHz. It is made of high quality materials under a high standard, the Attenuation Value of this product is ①01-03 dB②20 dB③30 dB, Attenuation Tolerance is ①±0.6 dB②±0.8 dB③±1.0 dB and VSWR Max is 1.25. The component has a good working performance and stability, it is ideal for handling a Rated Power of 250 W.

Product Details

Part Number	RFTXX-250AM1010-1.5
Description	DC~1.5 GHz Leaded Attenuator

General Parameters

Frequency Range	DC~1.5 GHz
Attenuation Value	①01-03 dB②20 dB③30 dB
Attenuation Tolerance	①±0.6 dB②±0.8 dB③±1.0 dB
VSWR Max	1.25
Rated Power	250 W
Impedance	50 Ω
Temperature Coefficient Max	150 ppm/°C
Size	Refer to the design drawing
Substrate Material	BeO
Porcelain Hat Material	Al ₂ O ₃
Lead	Silver-plating copper
Resistance Technology	Thick Film
Operating Temperature	-55 to +150 °C
ROHS Compliant	Yes

Outline Drawing (mm)

