



RF Solution offer a wide selection of Microstrip Attenuator for global customers. RFTXX-50MA2525-4 is a Microstrip Attenuator in Frequency Range of DC~4.0 GHz. It is made of high quality materials under a high standard, the Attenuation Value of this product is ①3/6/10 dB ②15/20 dB ③30 dB, Attenuation Tolerance is ①±0.6 dB ②±0.8 dB ③± 1.0 dB and VSWR Max is 1.25 type 1.30. The component has a good working performance and stability, it is ideal for handling a Rated Power of 50 W.

Product Details

Part Number	RFTXX-50MA2525-4
Description	DC~4.0 GHz Microstrip Attenuator

General Parameters

Frequency Range	DC~4.0 GHz
Attenuation Value	①3/6/10 dB ②15/20 dB ③30 dB
Attenuation Tolerance	①±0.6 dB ②±0.8 dB ③± 1.0 dB
VSWR Max	1.25 type 1.30
Rated Power	50 W
Impedance	50 Ω
Size	25.5.0*25.5*3.2 mm
Temperature Coefficient Max	150 ppm/°C
Substrate Material	BeO
Resistance Process	Thick Film
Operating Temperature	-55~+150 °C
Storage Temperature	/
ROHS Compliant	Yes

Outline Drawing (mm)

