



RF Solution offer a wide selection of Microstrip Attenuator for global customers. RFTXXA-02MA5263-12.4 is a Microstrip Attenuator in Frequency Range of DC~12.4 GHz. It is made of high quality materials under a high standard, the Attenuation Value of this product is ①1-10 dB ②11-20 dB ③30 dB, Attenuation Tolerance is ①±0.5 dB ②±1.0 dB ③±1.0 dB and VSWR Max is 1.20 @10GHz, 1.25@12.4GHz. The component has a good working performance and stability, it is ideal for handling a Rated Power of 2 W.

Product Details

Part Number	RFTXXA-02MA5263-12.4
Description	DC~12.4 GHz Microstrip Attenuator

General Parameters

Frequency Range	DC~12.4 GHz
Attenuation Value	①1-10 dB ②11-20 dB ③30 dB
Attenuation Tolerance	①±0.5 dB ②±1.0 dB ③±1.0 dB
VSWR Max	1.20 @10GHz, 1.25@12.4GHz
Rated Power	2 W
Impedance	50 Ω
Size	6.35*5.2*0.5 mm
Temperature Coefficient Max	150 ppm/°C
Substrate Material	Al2O3
Resistance Process	Thick Film
Operating Temperature	-55~+150 °C
Storage Temperature	/
ROHS Compliant	Yes



Outline Drawing (mm)

