



RF Solution offer a wide selection of Microstrip Attenuator with Sleeve for global customers. RFTXXN-10TA7412-6 is a Microstrip Attenuator with Sleeve in Frequency Range of DC~6.0 GHz. It is made of high quality materials under a high standard, the Attenuation Value of this product is ①01-10 dB ②11-20 dB ③21-30 dB ④40 dB, Attenuation Tolerance is ①±0.6 dB ②±0.7 dB ③± 1.0 dB ④± 1.0 dB and VSWR Max is 1.25 type 1.3. The component has a good working performance and stability, it is ideal for handling a Power of 10 W.

Product Details

Part Number	RFTXXN-10TA7412-6
Description	DC~6.0 GHz Microstrip Attenuator With Sleeve

General Parameters

Frequency Range	DC~6.0 GHz
Attenuation Value	①01-10 dB ②11-20 dB ③21-30 dB ④40 dB
Attenuation Tolerance	①±0.6 dB ②±0.7 dB ③± 1.0 dB ④± 1.0 dB
VSWR Max	1.25 type 1.3
Power	10 W
Impedance	50 Ω
Size	Φ7.4*11.8 mm
Temperature Coefficient Max	150 ppm/°C
Substrate Material	AlN
Sleeve Material	Al (Conductive oxidation)
Resistance Process	Thick Film
Operating Temperature	-55 ~+125°C
ROHS Compliant	Yes



Outline Drawing (mm)

