



RF Solution offer a wide selection of Coaxial Isolator for global customers. TG4550XS is a Coaxial Isolator in Frequency Range of 250~1400 MHz. It is made of high quality materials under a high standard, the Bandwidth Max of this product is 40%, Insertion Loss Max is 0.25~0.80 dB and Isolation Min is 18.0~23.0 dB. The component has a good working performance and stability, it is ideal for handling a Forward Power of 100 W.

## **Product Details**

| Part Number | TG4550XS                         |
|-------------|----------------------------------|
| Description | 250 to 1400 MHz Coaxial Isolator |

## **General Parameters**

| Frequency Range       | 250~1400 MHz          |
|-----------------------|-----------------------|
| Bandwidth Max         | 40%                   |
| Insertion Loss Max    | 0.25~0.80 dB          |
| Isolation Min         | 18.0~23.0 dB          |
| Forward Power         | 100 W                 |
| Reverse Power         | 20/100 W              |
| VSWR Max              | 1.20~1.40             |
| Impedance             | 50 Ω                  |
| Connector Type        | N-F                   |
| Size                  | 45.0*49.0*18.0 mm     |
| Weight                | ≈260 g                |
| Operating Temperature | -30~+70 °C/-40~+85 °C |
| Storage Temperature   | -50~+90 °C            |
| ROHS Compliant        | Yes                   |



## **Outline Drawing (mm)**

