



RF Solution offer a wide selection of Dual Junction Isolator for global customers. UIYCDI7048A is a Dual Junction Isolator in Frequency Range of $200\sim1875$ MHz. It is made of high quality materials under a high standard, the Bandwidth Max of this product is 30%, Insertion Loss Max is $0.40\sim1.30$ dB and Isolation Min is $30.0\sim60.0$ dB. The component has a good working performance and stability, it is ideal for handling a Forward Power of 100/300 W.

Product Details

| Part Number | UIYCDI7048A |
|-------------|--|
| Description | 200 to 1875 MHz Dual Junction Isolator |

General Parameters

| Frequency Range | 200~1875 MHz |
|-----------------------|--|
| Bandwidth Max | 30% |
| Insertion Loss Max | 0.40~1.30 dB |
| Isolation Min | 30.0~60.0 dB |
| Forward Power | 100/300 W |
| Reverse Power | 100 W |
| VSWR Max | 1.15~1.45 |
| Impedance | 50 Ω |
| Connector Type | SMA-F/N-F/N-M |
| Size | 70×48.5×15 mm |
| Weight | I and the second |
| Operating Temperature | -40~+85 °C |
| Storage Temperature | 1 |
| ROHS Compliant | Yes |



Outline Drawing (mm)

